

FIG. 1



FIG. 2(A)



FIG. 2(B)


A
B
C
CYCLE 1
Ø1
ACCEPT
Ø0
CYCLE 2
Ø1
Ø0
CYCLE 3
Ø1
Ø0
CYCLE 4
Ø1
D3
D4
D5
H

FIG. 3A-1



FIG. 3A-2



FIG. 3B-1



FIG. 3B-2



FIG. 4



FIG. 5(A)


PH0
PH1
NOT_RESET
04
00
04
ff
00
IN_DATA
IN_VALID
IN_ACCEPT
00
04
ff
D_LDOUT
Q_{AIN}
Q_{AOUT}
cc
00
04
ff
OUT_DATA
OUT_VALID
OUT_ACCEPT
630 670 710 750 790 830 870
TIME

FIG. 5(B)


PH1
PHØ
IN_DATA(7:0)
D Q
CK Q̄
MD(7:0)
MD(2)
N_MD(7:0)
LDIN
D Q
CK
LDOUT
OUT_DATA(7:0)
NAND1
N_MD(7)
N_MD(6)
N_MD(5)
N_MD(4)
N_MD(3)
NAND2
NOR1
SA
D Q
CK
LADDR
DATA_ADDR
D Q
QEPREV
CK
LEPREV
IN_EXTN
D Q
CK
LEIN
D Q
CK
LEOUT
OUT_EXTN

FIG. 6



FIG. 7


PH1
PHØ
IN_DATA(7:0)
D Q
CK
LD IN
MID-DATA(7:0)
MID-ACCEPT
IN_EXTN
LE IN
INV10
S4
NAND 10
NOT_RESET_O
IN_VALID
LV IN
INV12
NAND 12
S5
IN_ACCEPT
INV 16
NAND 16
LAIN
Q D
NAND 14
INV14
NOR1
MID-DATA (7)
MID-DATA (6)
MID-DATA (5)
MID-DATA (4)
MID-DATA (3)
MID-DATA (2)
NAND18
NOR2
S1
LI1
LI2
LI3
NAND20
S2
NAND22
S3
NAND24

FIG. 8(A)


D Q
CK
LD OUT
OUT_DATA(7:0)
D Q
CK
LE OUT
OUT_EXTN
MID-EXTN
NAND 30
INV30
OUT_VALID
D R Q
CK
LV OUT
NAND
28
INV
28
OUT_ACCEPT
Q D
CK
LA OUT
NAND
26
INV
26
56
LO1
LO2
DATA_TOKEN
LO3
NOT_DUPLICATE

FIG. 8(B)


PHØ
PH1
NOT_RESET
IN_EXTN
IN_DATA
cc
00
33
00
aa
00
IN_VALID
IN_ACCEPT
MID_EXTN
MID_DATA
55
cc
00
33
00
aa
00
MID_VALID
MID_ACCEPT
OUT_EXTN
OUT_DATA
55
cc
00
33
00
aa
00
OUT_VALID
OUT_ACCEPT
DATA_TOKEN
NOT_DUPLICATE
923
988
1053
1118
1183
1248
1313
TIME

FIG. 9(B)



FIG. 9(A)


43
44
Register
Register
46
Token
Decode
33
40
Action
Identification
39
32
37
38
Input
Latches
34
35
Processing Unit
36
Output
Latches
41
42
31

FIG. 10



FIG. 11


EXTERNAL
DRAM
91
ADDRESS
GENERATOR
94
99
DRAM
INTERFACE
100
102
108
PRED
FILTER
103
107
93
104
92
FORK
91
95
FIFO
96
97
+
98
105
OUPUT
SELECTOR
106
109
TO
(FIG. 13)

FIG. 12



FIG. 13



FIG. 14a



FIG. 14b



FIG. 14c


H.261
MPEG
JPEG

FIG. 15


162
161
PICTURE-START
163
PICTURE-END
164
166
165
PICTURE-START
167
PICTURE-END
168

FIG. 16



FIG. 17


FORWARD PREDICTION FILTER 201
BACKWARD PREDICTION FILTER 204
202
205
+
203
206

FIG. 18



FIG. 19



FIG.20


START CODE 243
START CODE 245
00 00 00 00 00 00 00 00 00 00 01 10 10 10 00 00 00 00 00 00 00 00 00 00 00 11 10 00 11 1
241
242
VALUE 244
246
VALUE 247

FIG. 21



FIG.22



FIG.23



FIG.24



FIG. 25



FIG. 26



FIG.27


INPUT DATA
FORMAT
331
1-D PREDICTION
X-COORDINATE
332
DIMENSION
BUFFER
333
1-D PREDICTION
Y-COORDINATE
334
OUTPUT DATA

FIG.28



FIG.29



FIG.30



FIG.31



FIG.32


extension bit
bits 7:0
0
1
1
1
1
1
0
6 word Token
1 word Token
0
Start of Token
1
1
End of Token
0

FIG.33


extension bit
bits 7 ... 0
E
7
6
5
4
3
2
1
0
1
A
A
A
A
D
D
D
D
1
D
D
D
D
D
D
D
D
0
D
D
D
D
D
D
D
D
3 word Token
A
Address field
D
Data field

FIG.34



FIG.35



MPEG 4:2:0
macroblock

FIG.36A

JPEG 2:1:1
macroblock

FIG.36B


clock
valid
accept
data
1
2
3
TIME

FIG.37


Coded video data
DRAM
Spatial Decoder
DRAM
Temporal Decoder
Control Microprocessor
DRAM
Image Formatter
Raster video data

FIG.38


Decoder clock propagation
Oscillator
system de-mux
Spatial Decoder
Temporal Decoder
Image Formatter
Data propagation

FIG.39


Clock
valid / accept
data / extn
3
1
2, 4
3
1
2, 4
TIME

FIG.40


Access Start
Data Transfer
Default State

FIG.41


RAS
DRAM_addr[10:0]
CAS[3:0]
WE
OE
DRAM_data[31:0]
8
7
TIME

FIG.42


5
6
RAS
DRAM_addr[10:0]
WE
Row address timing
CAS[3:0]
OE
data[31:0]
Start of read
CAS[3:0]
OE
data[31:0]
Start of write
7
CAS[3:0]
OE
data[31:0]
Start of refresh
TIME

FIG.43


Access Start
Data Transfer
Data Transfer
6
8
8
RAS
5
DRAM_addr[10:0]
7
CAS[3:0]
WE
OE
DRAM_data[31:0]
TIME

FIG.44


RAS
DRAM_addr[10:0]
CAS[3:0]
WE
OE
DRAM_data[31:0]
8
7
TIME

FIG.45


RAS
DRAM_addr[10:0]
CAS[3:0]
WE
OE
DRAM_data[31:0]
8
7
TIME

FIG.46


RAS
DRAM_addr[10:0]
CAS[3:0]
WE
OE
DRAM_data[31:0]
9
TIME

FIG.47


Hidden bits
23:22
High column address bits
21:15
Row address
14:6
Low column address bits
5:2
Byte select
1:0
8:0
Row address bits
10:4
Column address bits
3:0

FIG.48



FIG.49



FIG.50


Any bus
19
20
21
22
Any strobe
TIME

FIG.51


CAS[3:0]
23
24
DRAM_data[31:0]
TIME

FIG.52


25
26
enable[1]
enable[0]
27
28
addr[7:0]
rw
30
32
29
31
data[7:0]
TIME

FIG.53


25
26
enable[1]
enable[0]
27
28
addr[9:0]
rw
33
34
data[7:0]
TIME

FIG.54



FIG.55



FIG.56



FIG.57



FIG.58



FIG.59



FIG.60


Non-data Tokens
Tokens from input circuit
Serial analysis of DATA Tokens for start codes
Additional Token insertion
Tokens to start-up control circuit

FIG.61


Long DATA Token
Start Code Detector
Start code detected and converted to Token
Short DATA Token

FIG.62


Non data Token inserted before start code
Start code in DATA Token
Start Code Detector

FIG.63


This looks like an MPEG picture start
0x00
0x00
0x01
0x00
0x00
0x01
0xB8
This looks like an MPEG group start

FIG.64


This looks like an MPEG slice start (0x28)
00000000 00000000 00000001 00101000 00000000 00000000 00001000
This looks like the prefix for a non-aligned MPEG start code

FIG.65


data discarded by discard all data or start code search
"new" video sequence
"old" video sequence
entry point for new video
end of "last" picture
filing system data blocks
FLUSH inserted to reset discard all mode

FIG.66


Detect end of picture and introduce PICTURE_END
Optionally stop after PICTURE_END and introduce a FLUSH following the PICTURE_END
Conditionally introduce SEQUENCE_START before PICTURE_START
Introduce CODING_STANDARD before SEQUENCE_START

FIG.67


Coded data buffer
Huffman decoder
Token buffer
From start code detector
Bit counter
Control logic
Output gate
To inverse modeller
Off-chip process

FIG.68


Coded data and Token buffers
D
C
B
A
Bit Counter
Enable Queue
Output Gate

FIG.69



FIG.70



FIG.71


Parser
Huffman Decoder
Macroblock Counter
ALU
Coded data and Tokens
from coded data buffer
Tokens to the Token
buffer

FIG.72


frame buffer
used by codec
horiz_macroblocks
a macroblock
valid area of
picture
vert_macroblocks

FIG.73



FIG.74A



FIG.74B



FIG.74C



FIG.74D

$$\begin{cases} \text{horiz\_macroblocks} = \dfrac{\text{horiz\_pels} + 15}{16} \\ \text{vert\_macroblocks} = \dfrac{\text{vert\_pels} + 15}{16} \end{cases}$$

FIG.75



FIG.76



FIG.77


Quantised values
Quantisation tables
Control logic
Post Processing

FIG.78


Scale factor
Quantised values
Quantisation tables
Post Processing
Control logic

FIG.79



FIG.80



FIG.8 I



FIG.82



FIG.83


Picture 1
Component 2
Picture 1
Component 1
Picture 1
Component 0
Picture 0
Component 2
Picture 0
Component 1
Picture 0
Component 0
component_offset_2
component_offset_1
component_offset_2
component_offset_1
picture_buffer_1
picture_buffer_0

FIG.84


Picture's
temporal
reference
0 3 1 2 6 4 5
I P B B P B B
Picture sequence in
coded data
0 1 2 3 4 5 6
I B B P B B P
Picture sequence
required for display

FIG.85



FIG.86



FIG.87



FIG.88


Picture buffer
Picture buffer
ΔP / I
previous P
or I

FIG.89


Picture buffer
Picture buffer
Motion vectors
Form
prediction
Error data

FIG.90



FIG.91



FIG.92


PICTURE_START
TEMPORAL_REFERENCE
PICTURE_TYPE
...
Picture formed of groups of blocks
PICTURE_END

FIG.93


CIF
0
1
2
3
4
5
6
7
8
9
10
11
QCIF
0
2
4

FIG.94



FIG.95

1	2	3	4	5	6	7	8	9	10	11
12	13	14	15	16	17	18	19	20	21	22
23	24	25	26	27	28	29	30	31	32	33

FIG.96



FIG.97



FIG.98

1	2	3	4	5	6	7	8
9	10	11	12	13	14	15	16

.
.
.

59	58	59	60	61	62	63	64

FIG.99



FIG. 100



FIG. 101



FIG. 102



FIG. 103



FIG. 104



FIG. 105



FIG. 106


Picture's temporal reference
First GOP
Second GOP
0 3 1 2 6 4 5
I P B B P B B
10 13 11 12 16 14 15
2 0 1 5 3 4
I B B P B B
19 17 18 22 20 21
Picture sequence in coded data
0 1 2 3 4 5 6
I B B P B B P
10 11 12 13 14 15 16
0 1 2 3 4 5
B B I B B P
17 18 19 20 21 22
Picture sequence at display
Picture's "frame number"
Picture 17 may depend on 16 and 19

FIG. 107

FIG. 108



FIG. 109



FIG. 110



FIG. 111



FIG. 112



FIG. 113



FIG. 114



FIG. 115



FIG. 116



FIG. 117


Parser State
Machine
In Shift
Huffman
Decoder
Index to
Data
ALU
Token
Formatter

FIG. 118


Read AC Coefficients
Decode Tcoeff VLC
Index = ESCAPE ?
Y
N
Read 6 bit FLC
Read 1 bit FLC
0 ?
Y
N
Read 7 bit FLC
0 ?
Y
N
Read 8 bit FLC
Index = EOB ?
Y
N
Read 1 bit FLC
Accept New Command
Read 7 bit FLC
0 ?
Y
N
Read 8 bit FLC

FIG. 119


Command from Demux
next bit
Huffman
Decode Logic
= EOB
= ZRL
Huffman
State Machine
Index to Data
SSSS
RUN
ALU
SIGN, LEVEL
RUN

FIG. 120



FIG. 121A



FIG. 121B



FIG. 122



FIG. 123


Command from Demux
next bit
Huffman
Decode Logic
= EOB
= ESCAPE
= 0
Huffman
State Machine
Index to Data
LEVEL or SIGN
or 7, 8 bit FLC
RUN
ALU
SIGN, LEVEL
RUN

FIG. 124



FIG.125


8
2-WIRE i/f
12
6
CONSTANT
INPUT DATA
RUN
EXT
ph0
INPUT BLOCK 400
ZERO DETECT
SCC
ZCC
SIGN
TO UPI
ZERO
CC VALID
CONDITION CODES 402
A REGISTER 403
ADD
INPUT
SGX
PEG
ph1
ph0
12
A
8
TO UPI
RUN 404
INPUT
ADD
6
RUN
6
TO UPI
A
REG
INPUT
ZERO
CONST
A
INPUT
INPUT1
+/-
INPUT2
405
12
ADD
INPUT
A
CONST
A
REG
RUN
DATA
SIGN
EXTEND
SIZE
406
12
SGX
SIGN
LEVEL
2-WIRE i/f
INPUT
A
ADD
ADDU4
SIGN
GND
S
17
RUN
RUN
GND
EXT
ph1
OUTPUT BLOCK 401
HARDWIRED MB
COUNTER STRUCTURE
ADDR
UPI ADDR
ADDRESS DECODE
ADD
SGX
UPI
12
12
REG
ph1
ph0
8
TO UPI
REGISTER FILE 407

FIG. 126



FIG. 127



FIG. 128



FIG. 129



FIG. 130


Address Generator
420
Data
Data
External
DRAM
422
DRAM Interface
421

FIG. 131


valid/accept
Control
Write Address
Read Address
RAM 1
Data In
430
Data Out
RAM 2

FIG. 132



FIG. 133



FIG. 134


BodyWord counter
63WordsInBody
TokenHeader
HeaderExtn
ExtnBit
PLA
NextSubstate
Address
Read/Write
Enable
InsertNext
Coefficients?

FIG. 135



FIG. 137



FIG. 138


Y[0]
Y[4]
Y[2]
Y[6]
Y[1]
Y[5]
Y[3]
Y[7]
X[0]
X[1]
X[3]
X[2]
X[7]
X[6]
X[4]
X[5]
c1s
c3s
c3s
c1s
√2
d1
d3
d7
d5
c1s
c3s
c3s
c1s
Key:-
coef
constant coefficient multiplier
adder,subtractor

FIG. 136


12
12 bit integer
decheck
DATA Error Checking and
Recovery
440
12
izz
Inverse Zig-Zag RAM
441
12
ip_fmt
Input Formatter
442
22
10 bits fraction
oned
1-D IDCT Transform
443
1st Dimension
22
7 bits fraction
tram
Inverse Zig-Zag RAM
444
22
oned
1-D IDCT Transform
445
2nd Dimension
22
4 bits fraction
ras
Round and Saturate
446
9
9 bit integer

FIG. 139


12
12 bit integer
decheck
12
uP port
izz
12
ip_fmt
22
10 bits fraction
uP port
snooper
22
oned
1st Dimension
22
7 bits fraction
uP port
tram
22
oned
2nd Dimension
22
4 bits fraction
uP port
snooper
22
ras
9
9 bit integer
uP port
super snooper
9

FIG. 140





NOTE: "COMMON BLOCK" IS ENTIRELY COMBINATIONAL (NO LATCHING)

FIG. 141



FIG. 142


in_data
in_valid
in_accept
ph1
ph0
ck
ck
ck
ck
ck
ck
Logic
out_data
out_valid
out_accept

FIG. 143


Token Input
Token Decode
Macroblock Counter
Block Calculation
Base Block Address
Vector Offset
Reorder Read Requests
Write Requests
Prediction Requests
DRAM Interface

FIG. 144



FIG. 145



FIG. 146


Input Data
Pred. Filters Formatter
1-D Prediction Filter (x)
Dimension Buffer
1-D Prediction Filter (y)
Output Data

FIG. 147



FIG. 148

0	1	2	3	4	5	6	7
8	9	10	11	12	13	14	15
16	17	18	19	20	21	22	23
24	25	26	27	28	29	30	31
32	33	34	35	36	37	38	39
40	41	42	43	44	45	46	47
48	49	50	51	52	53	54	55
56	57	58	59	60	61	62	63

FIG. 149


Reorder Input
Token Input
FIFO 1
FIFO 2
Output
Token Decode
Token Input Control
FIFO Input Interface
Output Control

FIG. 150



FIG. 151



FIG. 152

Read Cycle



FIG. 153

Write Cycle



FIG. 154


NEΦ
NEΦ
RΦ
RΦ
UPSAMVO FIFO
UPSAMV1
UPSAMV2
10
UPSAMHO
UPSAMH1
UPSAMH2
9
NEΦ
COLOUR-SPACE CONVERSION
GAMMAO
GAMMA 1
GAMMA2
8
RΦ
OUTPUT CONTROLLER
S
28
DΦ FIFO
DΦ BUFFER MANAGER
TOKENS WRITE INDEX
PICTURE clk
READ INDEX
CLOCK DIVIDERS
PICTURE clk
AUDIO clk
2
WΦ TOKENS INDEX
WRITE ADDRESS GENERATION
DATA ADDRESS
DΦ INDEX
READ ADDRESS GENERATION
ADDRESSO ADDRESS1 ADDRESS2
18
26
WRITE DATA
WRITE ADDRESS
READ ADDRESS 0
READ ADDRESS 1
READ ADDRESS 2
DRAM INTERFACE
OUTΦ
clk
bifRΦ
READ DATA 0
READ DATA 1
READ DATA 2
S =SUPER SNOOPER
s =SNOOPER

FIG. 155


ph0
ph1
pic_clk
pic_ph0
prev_pic_ph0
prn_chg
en_prnum
new_incr_prn
incr_prn
prnum
pres_flag
For convenience pic_clk is shown simply re-timed to ph0; in reality this is properly synchronised.
pres_num
pres_num+1
state = PRES0
or TOKEN
TIME

FIG. 156


START
PRESO
increment index
OTHERS
PRESI
VACATE_RDY
clear old rdy
!pres_flg ! allocated
DRQ
from_ps
ALLOC
x!=max & !vacant
!x=max & !vacant
from_n
clear disp
else
FLUSH
ix==max & (vacant ! in use as disp)
else
else
VACATE_DISP
use rdy
TOKEN
pic_start ! flush ! !valid ! laccept
USE_RDY
picture end
tr&H26I
else
OUTPUT_TAIL
in_extn_reg
TEMP_REFO
NEW_EXP_TR
PIC_END
ix!=arr
ix==arr & rdytst & rdy!=0
TEMP_REF1
SET_ARR_IX
else
TEMP_REF2
NEW_PIC_NUM
TEMP_REF3

FIG. 157


PRESO
increment
index
PRES1
!pres_flg | allocated
DRQ
TOKEN
pic_start | flush | !valid | !accept

FIG. 158



FIG. 159A



FIG. 159B



FIG. 159C



FIG. 160

BUFFER OFFSET 0x00

COMPONENT OFFSET 0x000 + ...

00	01	02	03	04	05	06	07	08	09	0A	0B
0C	0D	0E	0F	10	11	12	13	14	15	16	17
18	19	1A	1B	1C	1D	1E	1F	20	21	22	23
24	25	26	27	28	29	2A	2B	2C	2D	2E	2F
30	31	32	33	34	35	36	37	38	39	3A	3B
3C	3D	3E	3F	40	41	42	43	44	45	46	47
48	49	4A	4B	4C	4D	4E	4F	50	51	52	53
54	55	56	57	58	59	5A	5B	5C	5D	5E	5F
60	61	62	63	64	65	66	67	68	69	6A	6B
6C	6D	6E	6F	70	71	72	73	74	75	76	77
78	79	7A	7B	7C	7D	7E	7F	80	81	82	83
84	85	86	87	88	89	8A	8B	8C	8D	8E	8F

FIG. 161A

COMPONENT1 OFFSET 0x100 + ...

00	01	02	03	04	05
06	07	08	09	0A	0B
0C	0D	0E	0F	10	11
12	13	14	15	16	17
18	19	1A	1B	1C	1D
1E	1F	20	21	22	23

FIG. 161B

COMPONENT1 OFFSET 0x200 + ...

00	01	02	03	04	05
06	07	08	09	0A	0B
0C	0D	0E	0F	10	11
12	13	14	15	16	17
18	19	1A	1B	1C	1D
1E	1F	20	21	22	23

FIG. 161C



FIG. 162



BLOCK ADDRESS=0+0+0x5D8+0x28+0x2C+1=0x62D

FIG. 163A



BLOCK ADDRESS=0+0+0+0x2A+0+0=0x2A

FIG. 163B


IDLE
idr data
idr define samp
fc
ADDR1
ADDR2
ADDR3
ADDR4
ADDR5
HB
!ivr
idr cod std
COD_STD
idr other
idr pic start
PIC_ST1
comp!=2
PIC_ST2
comp!=2
PIC_ST3
HSAMP
VSAMP
!(ivr&!ixr)
idr hmbs
OUTPUT_TAIL
idr vmbs
HORZ_MBS1
HORZ_MBS0
VERT_MBS1
VERT_MBS0
fc+!aar
fc.!z
MB0
z
MB1
MB2
MB3
MB4
MB5
MB6
** = !z&!H261&fc+!z&H261&(QCIF+fc)+z&H261&QCIF
= return to IDLE
fc = first cycle
z = zero flag
OTHER
!(ivr&rar&!ixr)
DATA
!z&!H261%!fc
MB4A
z&H261&!QCIF&
!mod3eq2
z&!mod
3eq2
!z&!fc
MB4B
!z&H261&!QCIF&!fc
z&mod3eq2&!fc
MB4C
MB4D

FIG. 164


UPI_DATA_BUS
LOADA_0
LOADB_0
UPI_WRITE_STROBES
PH1
UPI_WRITE_STROBES
DRIVEA_SELECTS
DRIVEB_SELECTS
UPI_BYTE_SELECTS
NUPIO[7:0]
VARIOUS CONSTANTS
SRCA[0]
SRCA[1]
SRCA[2]
SRCA[3]
SRCA[4]
SRCA[5]
SRCB[0]
SRCB[1]
SRCB[2]
SRCB[3]
SRCB[4]
SRCB[5]
COUT
CIN
PH0
PH0
FC
N
U
CBUS[17:0]

FIG. 165



FIG. 166



FIG. 167



FIG. 168


x0
L
c01
c11
Register
Register
x1
L
R
c02
c12
Adder
Adder
Register
Register
x2
L
R
R
c03
c13
Adder
Adder
Register
Register
c04
c14
Add & Resolve
Add & Resolve
Register
Register
Saturate
Saturate
Latch
Latch
out_data0
out_data1

FIG. 169